OCT 4 1990

FEMA:390670

FLOOD INSURANCE STUDY

VILLAGE OF RUTLAND, OHIO

MEIGS COUNTY

NOVEMBER 2, 1990

Federal Emergency Management Agency

COMMUNITY NUMBER - 390670

NOTICE TO
FLOOD INSURANCE STUDY USERS

Communities participating in the National Flood Insurance Program have established repositories of flood hazard data for floodplain management and flood insurance purposes. This Flood Insurance Study may not contain all data available within the repository. It is advisable to contact the community repository for any additional data.

TABLE OF CONTENTS

		Page
1.0	INTRODUCTION	1
1.1	Purpose of Study	1
1.2	Authority and Acknowledgments	1
1.3	Coordination	1
2.0	AREA STUDIED	2
2.1	Scope of Study	2
2.2	Community Description	2
2.3	Principal Flood Problems	2
2.4	Flood Protection Measures	2
3.0	ENGINEERING METHODS	2
3.1	Hydrologic Analyses	4
3.2	Hydraulic Analyses	4
4.0	FLOODPLAIN MANAGEMENT APPLICATIONS	5
4.1	Floodplain Boundaries	5
4.2	Floodways	6
5.0	INSURANCE APPLICATION	6
6.0	FLOOD INSURANCE RATE MAP	8
7.0	OTHER STUDIES	9
8.0	LOCATION OF DATA	9
9.0	REFERENCES AND BIBLIOGRAPHY	9

TABLE OF CONTENTS (continued)

Page

FIGURES

Figure 1 - Vicinity Map 3

Figure 2 - Floodway Schematic 8

TABLES

Table 1 - Summary of Discharges 4

Table 2 - Floodway Data 7

EXHIBITS

Flood Profiles

Little Leading Creek Panel 01P

Flood Insurance Rate Map

Elevation Reference Marks

FLOOD INSURANCE STUDY

VILLAGE OF RUTLAND,
MEIGS COUNTY,
OHIO

1.0 INTRODUCTION

1.1 Purpose of Study

This Flood Insurance Study investigates the existence and severity of flood hazards in the Village of Rutland, Meigs County, Ohio, and aids in the administration of the National Flood Insurance Act of 1968 and the Flood Disaster Protection Act of 1973. This study has developed flood risk data for various areas of the community that will be used to establish actuarial flood insurance rates and assist the community in its efforts to promote sound floodplain management. Minimum floodplain management requirements for participation in the National Flood Insurance Program are set forth in the Code of Federal Regulations at 44 CFR, 60.3.

In some states or communities, floodplain management criteria or regulations may exist that are more restrictive or comprehensive than the minimum Federal requirements. In such cases, the more restrictive criteria take precedence and the State (or other jurisdictional agency) will be able to explain them.

1.2 Authority and Acknowledgments

The hydrologic and hydraulic analyses for this study were performed by the U.S. Geological Survey, Water Resources Division (the Study Contractor) for the Federal Emergency Management Agency (FEMA), under Inter-Agency Agreement No. EMW-88-E-2738, Project Order No. 1. This study was completed in October 1988.

1.3 Coordination

On August 20, 1987, an initial coordination meeting was held with representatives of FEMA; the Ohio Department of Natural Resources, Division of Water; the Village of Rutland; and the Study Contractor. Coordination with village officials and Federal and State agencies produced a variety of information pertaining to floodplain regulations, community maps, flood history, and other hydrologic data.

On December 5, 1989, the results of this Flood Insurance Study were reviewed and accepted at a final coordination meeting attended by representatives of the Study Contractor, FEMA, and the community.

2.0 AREA STUDIED

2.1 Scope of Study

This Flood Insurance Study covers the incorporated area of the Village of Rutland, Meigs County, Ohio. The area of study is shown on the Vicinity Map (Figure 1).

Flooding caused by overflow of Little Leading Creek was studied in detail.

Approximate analyses were used to study those areas having low development potential or minimal flood hazards.

The areas studied were selected with priority given to all known flood hazard areas and areas of projected development or proposed construction through October 1993. The scope and methods of study were proposed to and agreed upon by FEMA and the Village of Rutland.

2.2 Community Description

The Village of Rutland is in southern Meigs County, approximately 5 miles west of the City of Pomeroy, and is served by State Route 124. The village is surrounded by the unincorporated areas of Meigs County. The 1980 population of Rutland was reported to be 635 (Reference 1).

The average annual precipitation in the village is approximately 40 inches and is evenly distributed throughout the year (Reference 2).

2.3 Principal Flood Problems

The low-lying areas adjacent to Little Leading Creek within the Village of Rutland are subject to periodic flooding.

2.4 Flood Protection Measures

Flood protection measures are not known to exist within the study area.

3.0 ENGINEERING METHODS

For the flooding sources studied in detail in the community, standard hydrologic and hydraulic study methods were used to determine the flood hazard data required for this study. Flood events of a magnitude that is expected to be equaled or exceeded once on the average during any 10-, 50-, 100-, or 500-year period (recurrence interval) have been selected as having special significance for floodplain management and for flood insurance rates. These events, commonly termed the 10-, 50-, 100-, and 500-year floods, have a 10-, 2-, 1-, and 0.2-percent chance, respectively, of being equaled or exceeded during any year. Although the recurrence interval represents the long-term average period between floods of a specific magnitude, rare floods could occur at short intervals or even within the same year. The risk of experiencing a rare flood increases when periods greater than 1 year are considered. For example, the risk of having a flood that equals or exceeds the 100-year flood (1-percent chance of annual exceedence) in any



FIGURE 1

FEDERAL EMERGENCY MANAGEMENT AGENCY

VILLAGE OF RUTLAND, OH
(MEIGS CO.)

APPROXIMATE SCALE

4 0 4 8 12 MILES

VICINITY MAP

50-year period is approximately 40-percent (4 in 10), and, for any 90-year period, the risk increases to approximately 60-percent (6 in 10). The analyses reported herein reflect flooding potentials based on conditions existing in the community at the time of completion of this study. Maps and flood elevations will be amended periodically to reflect future changes.

3.1 Hydrologic Analyses

Hydrologic analyses were carried out to establish the peak discharge-frequency relationships for each riverine flooding source studied in detail affecting the community.

The magnitude of the discharges for the 100-year recurrence interval flood was determined by methods outlined in Ohio Bulletin No. 45 (Reference 3). These methods consist of regression equations that utilize topographic and climatological characteristics of the basin, based on regional analysis, to develop a flood-frequency curve. The equations are power equations based on drainage area and main-channel slope. There are no stream-gage data available for Little Leading Creek; therefore, no adjustments were made to the calculated discharges.

Peak discharge-drainage area relationships for the 100-year flood of Little Leading Creek are shown in Table 1.

TABLE 1 - SUMMARY OF DISCHARGES

FLOODING SOURCE AND LOCATION	DRAINAGE AREA (SQ MILES)	PEAK DISCHARGE (CFS) 100-YEAR
LITTLE LEADING CREEK		
about 5,100 feet above mouth	25.0	3,620
about 950 feet downstream of Main Street bridge	21.2	3,410

3.2 Hydraulic Analyses

Analyses of the hydraulic characteristics of flooding from the sources studied were carried out to provide estimates of the elevations of floods of the selected recurrence intervals.

Cross-section data, as well as structural geometry and elevations for bridges, were determined from field surveys.

Locations of selected cross sections used in the hydraulic analyses are shown on the Flood Profiles and on the Flood Insurance Rate Map.

Roughness coefficients (Manning's "n") for Little Leading Creek range from 0.030 to 0.065 for the channel and from 0.03 to 0.10 for the overbank areas.

Water-surface elevations for the 100-year flood were computed using WSPRO, a step-backwater computer program (Reference 4). The starting water-surface elevation for Little Leading Creek was determined using the slope-conveyance method.

Flood profiles were drawn showing the computed water-surface elevations for floods of the selected recurrence intervals.

The hydraulic analyses for this study are based on the effects of unobstructed flow. The flood elevations shown on the profiles are thus considered valid only if hydraulic structures remain unobstructed, operate properly, and do not fail.

All elevations are referenced to the National Geodetic Vertical Datum of 1929 (NGVD). Elevation reference marks used in this study are shown on the map and described in the exhibit labeled Elevation Reference Marks.

4.0 FLOODPLAIN MANAGEMENT APPLICATIONS

The National Flood Insurance Program encourages State and local governments to adopt sound floodplain management programs. Therefore, each Flood Insurance Study provides 100-year flood elevations and delineations of the 100- and 500-year floodplain boundaries and 100-year floodway to assist communities in developing floodplain management measures.

4.1 Floodplain Boundaries

To provide a national standard without regional discrimination, the 1-percent annual chance (100-year) flood has been adopted by FEMA as the base flood for floodplain management purposes. The 0.2-percent annual chance (500-year) flood is employed to indicate additional areas of flood risk in the community. For each stream studied in detail, the 100- and 500-year floodplain boundaries have been delineated using the flood elevations determined at each cross section. Between cross sections, the boundaries were interpolated using topographic maps at a scale of 1:24000 with a contour interval of 20 feet (Reference 5).

The 100-year floodplain boundaries are shown on the Flood Insurance Rate Map. On this map, the 100-year floodplain boundary corresponds to the boundary of the areas of special flood hazards (Zones A, AE, AH, AO, A99, V, and VE). Small areas within the floodplain boundaries may lie above the flood elevations but cannot be shown due to limitations of the map scale and/or lack of detailed topographic data.

For the streams studied by approximate methods, only the 100-year floodplain boundary was delineated using the Flood Hazard Boundary Map for the Village of Rutland, Meigs County, Ohio (Reference 6).

4.2 Floodways

Encroachment on floodplains, such as structures and fill, reduces the flood-carrying capacity, increases the flood heights and velocities, and increases flood hazards in areas beyond the encroachment itself. One aspect of floodplain management involves balancing the economic gain from floodplain development against the resulting increase in flood hazard. For purposes of the National Flood Insurance Program, a floodway is used as a tool to assist local communities in this aspect of floodplain management. Under this concept, the area of the 100-year floodplain is divided into a floodway and a floodway fringe. The floodway is the channel of a stream plus any adjacent floodplain areas that must be kept free of encroachment so that the 100-year flood can be carried without substantial increases in flood heights. Minimum Federal standards limit such increases to 1.0 foot, provided that hazardous velocities are not produced. The floodways in this study are presented to local agencies as minimum standards that can be adopted directly or that can be used as a basis for additional floodway studies.

The floodways for this study were computed for certain stream segments on the basis of equal conveyance reduction from each side of the floodplain. Floodway widths were computed at cross sections. Between cross sections, the floodway boundaries were interpolated. The results of the floodway computations are tabulated for selected cross sections and are shown in Table 2, Floodway Data. The computed floodways are shown on the Flood Insurance Rate Map. In cases where the floodway and 100-year floodplain boundaries are either close together or collinear, only the floodway boundary is shown.

Along streams where floodways have not been computed, the community must ensure that the cumulative effect of development in the floodplain will not cause more than 1.0-foot increase in the base flood elevations at any point within the community.

The area between the floodway and the 100-year floodplain boundaries is termed the floodway fringe. The floodway fringe encompasses the portion of the floodplain that could be completely obstructed without increasing the water-surface elevation of the 100-year flood by more than 1.0 foot at any point. Typical relationships between the floodway and the floodway fringe and their significance to floodplain development are shown in Figure 2.

5.0 INSURANCE APPLICATION

For flood insurance rating purposes, flood insurance zone designations are assigned to a community based on the results of the engineering analyses. These zones are as follows:

FLOODING SOURCE		FLOODWAY			BASE FLOOD WATER SURFACE ELEVATION			
CROSS SECTION	DISTANCE[1]	WIDTH (FEET)	SECTION AREA (SQ. FEET)	MEAN VELOCITY (FEET/SEC.)	REGULATORY (FEET NGVD)	WITHOUT FLOODWAY (FEET NGVD)	WITH FLOODWAY (FEET NGVD)	INCREASE (FEET)
LITTLE LEADING CREEK								
A	5135	391	2230	1.6	573.2	573.2	574.0	0.8
B	5715	322	1726	2.1	573.4	573.4	574.2	0.8
C	6495	171	1043	3.5	574.2	574.2	574.8	0.6
D	7800	188	1081	3.4	575.9	575.9	576.8	0.9
E	8350	258	1567	2.3	576.4	576.4	577.4	1.0
F	9530	298	1400	2.6	577.8	577.8	578.5	0.7
G	10,360	220	1186	2.9	578.8	578.8	579.6	0.8
H	10,930	197	919	3.7	579.1	579.1	579.9	0.8
I	11,310	174	924	3.7	579.6	579.6	580.4	0.8
J	11,755	247	1169	2.9	580.3	580.3	581.0	0.7
K	12,565	340	1506	2.3	581.0	581.0	582.0	1.0

[1]FEET ABOVE MOUTH

TABLE 2

FEDERAL EMERGENCY MANAGEMENT AGENCY

VILLAGE OF RUTLAND, OH
(MEIGS CO.)

FLOODWAY DATA

LITTLE LEADING CREEK


100-YEAR FLOOD PLAIN
FLOODWAY FRINGE
FLOODWAY
FLOODWAY FRINGE
STREAM CHANNEL
FLOOD ELEVATION WHEN CONFINED WITHIN FLOODWAY
ENCROACHMENT
ENCROACHMENT
C
D
SURCHARGE*
A
B
AREA OF FLOOD PLAIN THAT COULD BE USED FOR DEVELOPMENT BY RAISING GROUND
FLOOD ELEVATION BEFORE ENCROACHMENT ON FLOOD PLAIN
LINE AB IS THE FLOOD ELEVATION BEFORE ENCROACHMENT.
LINE CD IS THE FLOOD ELEVATION AFTER ENCROACHMENT.
*SURCHARGE IS NOT TO EXCEED 1.0 FOOT (FEMA REQUIREMENT) OR LESSER AMOUNT IF SPECIFIED BY STATE

FIGURE 2 - Floodway Schematic

Zone A

Zone A is the flood insurance rate zone that corresponds to the 100-year floodplains that are determined in the Flood Insurance Study by approximate methods. Because detailed hydraulic analyses are not performed for such areas, no base flood elevations or depths are shown within this zone.

Zone AE

Zone AE is the flood insurance rate zone that corresponds to the 100-year floodplains that are determined in the Flood Insurance Study by detailed methods. Whole-foot base flood elevations derived from the detailed hydraulic analyses are shown at selected intervals within this zone.

Zone X

Zone X is the flood insurance rate zone that corresponds to areas outside the 100-year floodplain, areas of 100-year flooding where average depths are less than 1 foot, areas of 100-year flooding where the contributing drainage area is less than 1 square mile, and areas protected from the 100-year flood by levees. No base flood elevations or depths are shown within this zone.

6.0 FLOOD INSURANCE RATE MAP

The Flood Insurance Rate Map is designed for flood insurance and floodplain management applications.

For flood insurance applications, the map designates flood insurance rate zones as described in Section 5.0 and, in the 100-year floodplains that were studied by detailed methods, shows selected whole-foot base flood elevations or average depths. Insurance agents use the zones and base flood elevations in conjunction with information on structures and their contents to assign premium rates for flood insurance policies.

For floodplain management applications, the map shows by tints, screens, and symbols the 100- and 500-year floodplains, the floodways, and the locations of selected cross sections used in the hydraulic analyses and floodway computations.

7.0 OTHER STUDIES

This Flood Insurance Study supersedes the previously printed Flood Hazard Boundary Map for the Village of Rutland, Meigs County, Ohio (Reference 6).

8.0 LOCATION OF DATA

Information concerning the pertinent data used in the preparation of this study can be obtained by contacting the Natural and Technological Hazards Division, FEMA, 175 West Jackson Boulevard, 4th Floor, Chicago, Illinois 60604-2698.

Future revisions may be made that do not result in the republishing of the Flood Insurance Study report. To assure that any user is aware of all revisions, it is advisable to contact the map repository of flood hazard data located in the community.

9.0 REFERENCES AND BIBLIOGRAPHY

1. U.S. Department of Commerce, Bureau of the Census, 1980 Census of Population, Number of Inhabitants, Ohio, Washington, D.C., February 1982.

2. Ohio Division of Water, Inventory Report No. 13, Hydrologic Atlas of Annual Precipitation, Temperature, Streamflow, and Water Loss in Ohio, 1962.

3. Ohio Department of Natural Resources, Division of Water, Bulletin No. 45, Floods in Ohio, Magnitude and Frequency, E.E. Webber and W.P. Bartlett Jr., May 1977.

4. U.S. Department of Transportation, Federal Highway Administration, Report No. FHWA/RD - 86/108, Bridge Waterways Analysis Model: Research Report, J.O. Shearman, W.H. Kirby, V.R. Snyder, and H.N. Flippo, July 1986.

5. U.S. Geological Survey, 7.5 Minute Series Topographic Maps, Scale 1:24000, Contour Interval 20 Feet: Rutland, Ohio, 1960, photorevised 1975.

6. U.S. Department of Housing and Urban Development, Federal Insurance Administration, Flood Hazard Boundary Map, Village of Rutland, Meigs County, Ohio, November 1974, revised 1976.

ELEVATION REFERENCE MARKS

REFERENCE MARK	FLOOD INSURANCE RATE MAP PANEL	ELEVATION (FEET NGVD)	DESCRIPTION OF LOCATION
1	0001	578.427	tablet stamped "V 207 1958" in top of east end of south abutment of Main Street bridge over Little Leading Creek
2	0001	573.720	standard tablet stamped "575 ADJ 1903" set vertically in southwest corner of brick cellar located about 100 feet east of Rutland Road, about 750 feet south of Main Street



01P	FEDERAL EMERGENCY MANAGEMENT AGENCY **VILLAGE OF RUTLAND, OH** (MEIGS CO.)	**FLOOD PROFILES** **LITTLE LEADING CREEK**